

ΤΥΠΟΣ ΛΙΠΑΝΤΙΚΟΥ AGIP	ΡΕΥΣΤΟΤΗΤ	ΙΔΙΟΤΗΤ	Ρευστ.100°C mm²/s	Ρευστ.40°C mm²/s	Ρευστ.-30°C mPa.s	Δείκτης ρευστότητ.	Σημείον αναφλ. °C	Σημείον κυλήσ. °C	Πυκνότης μάζης 15°C kg/m³	ACEA	API	VAG	MERCEDES	ΑΛΛΑΙ
7007	0W/30	100% ΣΥΝΘ.	9,60	53,0	6000	167	223	-39	0,856	A5,B5		503,00-506,01		
SINT EVOLUTION	0W/30	100% ΣΥΝΘ.	12,00	73,0	6000	162	220	-39	0,855	A3,B3,B4	SJ/CF	502,00-505,00		BMW LONG 01
7006	0W/40	100% ΣΥΝΘ.	13,20	71,7	5600	186	225	-54	0,875			503,01		
TECSINT SX	0W/40	100% ΣΥΝΘ.	14,00	78,0	6600	182	216	-42	0,860	A3,B3,B4	SL/CF	502,00-505,00	229.3	
7008	5W/30	100% ΣΥΝΘ.	11,80	72,0	6000	160	235	-45	0,850			504,00-507,00		
FORMULA FUTURE	5W/30	100% ΣΥΝΘ.	12,00	74,0		161	240	-42		C2/C3-04-A3/B4		III 504,00-507,00	229.31-229.51	BMW LONG
TECSINT	5W/30	ΣΥΝΘ.ΒΑΣ.	11,80	64,5		173	225	-42	0,880	A3,B3,B4	SL/CF	502,00-505,00	229.3	
FORMULA LL DC	5W/30	ΣΥΝΘ.ΒΑΣ.	11,90	64,0	6200	165	250	-52	0,859	A3,B3,B4	SJ/CF		MB 229,5	
FORMULA LL FO	5W/30	ΣΥΝΘ.ΒΑΣ.	9,85	55,8		164	224	-45		A1,B1	SL			FORD/JAGUAR
FORMULA LL GM	5W/30	SPECIAL	11,80	70,5		165	234	-42		A3,B3	SL/CF			OPEL GM
FORMULA MS B04	5W/30	SPECIAL	12,40	75,0		165	248	-39	0,851	A3/B3,A3/B4, C3	SL/CF	502,00-505,00	MB 229,31	BMW LONG 04
TRUCK SINT	5W/30	100% ΣΥΝΘ.	12,00	75,0	6300	156	220	-40	0,855	E4	CF		MB 228,5	MAN M3277
EXTRA HTS	5W/40	100% ΣΥΝΘ.	14,30	85,0	6500	176	220	-39	0,850	A3/B3,A3/B4	SL/CF	502,00-505,00	MB 229,3	BMW LONG 01
TECSINT SL	5W/40	100% ΣΥΝΘ.	14,10	93,0	6300	155	220	-39	0,851	A3,B3,B4	SM/CF	502,00-505,00	MB 229,3	BMW LONG 01
SINT EVOLUTION	5W/40	100% ΣΥΝΘ.	12,00	73,0	6000	162	220	-39	0,855	A3,B3,B4	SL/CF	502,00-505,00		BMW LONG 01
SINT EVOLUTION TD	5W/40	100% ΣΥΝΘ.	14,20	94,0	6400	151	220	-39	0,854	B3,B4	CF	505,00	MB 229,3	GM LL-B-025
7004	5W/40	ΣΥΝΘ.ΒΑΣ.	14,10	89,0	6400	163	225	-40	0,856		SL	500,00-505,01		
FORMULA PRESTIGE	5W/40	100% ΣΥΝΘ.	13,10	76,0	6200	174	230	-36	0,852	C3.A3/B3/B4	SM/CF	502,00-505,00	MB 229,51	BMW LONG 04
COMMON RAIL	5W/40	ΣΥΝΘ.ΒΑΣ.	14,30	85,0	6300	176	220	-39	0,852	B3,B4	CF	505,00		GM LL-B-025
MULTITECH 2000	10W/30	ΣΥΝΘ.ΒΑΣ.	11,00			135	210	-30	0,880		CF-4/CE/SF			D4/G2
FORMULA LL PLUS	10W/40	ΣΥΝΘ.ΒΑΣ.	14,10	95,0	6800	152	220	-30	0,873	A3,B3	229.5	500,00-505,00		
SINT 2000	10W/40	ΣΥΝΘ.ΒΑΣ.	14,20	88,0	6700	167	225	-36	0,875	A3,B3	SJ/CF	500,00-505,00		GM 6094M
SINT 2000 TURBO D	10W/40	ΣΥΝΘ.ΒΑΣ.	14,10	95,0	6800	154	220	-30	0,873	A3,B3,B4	CF/SH	505,00		
ULTRA TFE	10W/40	ΟΡΥΚΤΕΛ.	13,30	87,0	6800	155	200	-33	0,868	E4	CF-4/SF		MB 228,5	MAN M3277
RACING	10W/60	100% ΣΥΝΘ.	24,00	160,0	6800	177	225	-33	0,890	A3,B3	SJ/CF			
UNIVERSAL MULTIFLEET	15W/40	ΟΡΥΚΤΕΛ.	14,60	106,0	6800	142	220	-30	0,885	A3,B3,B4,E2	SL/CF-4	501,00-505,00	MB 229,1	MAN 271
F.1 SUPERMOTOROIL	15W/40	ΟΡΥΚΤΕΛ.	14,50	109,0	6800	130	210	-24	0,884	A3,B3	SJ/CF	501,00-505,00		
SUPERDIESEL MULTIGR.	15W/40	ΟΡΥΚΤΕΛ.	14,50	110,0	6800	135	220		0,884	A2,B2	CF4/SG		MB 227,1	
SIGMA TURBO	15W/40	ΟΡΥΚΤΕΛ.	13,70	100,0	6700	138	230	-27	0,885	E3	CG4/SG		MB 228,3	MAN 3275
SIGMA TRUCK	15W/40	ΟΡΥΚΤΕΛ.	13,70	100,0	6700	138	230	-27	0,885	E7,E5,E3,B3	CI-4/CH-4/SL		MB 228,3	MAN 3275
SUPERTRACTOR	15W/40	ΟΡΥΚΤΕΛ.	13,60	100,0		135	220	-27	0,884		CE/SF-GL4		MB 227,1	
CLASSIC MOTOROIL	15W/50	ΟΡΥΚΤΕΛ.	17,50	120,0	6700	161	220	-30	0,882		SF/CC			G2/D1
SIGMA TURBO	20W/50	ΟΡΥΚΤΕΛ.	20,00	180,0		129	230	-21	0,891	E3	CF-4/SG			MAN QC 13-017
SUPERDIESEL MULTIGR.	20W/50	ΟΡΥΚΤΕΛ.	20,00	171,0		135	230	-24	0,897	E2,B2	CF4/SG		MB 228,1	MAN 271
SUPERMOTOROIL	20W/50	ΟΡΥΚΤΕΛ.	18,30	156,0		131	225	-27	0,893		SF/CC			
DIESEL SIGMA	10W/20	ΟΡΥΚΤΕΛ.	6,80	42,0	6700	118	225	-30	0,877		CD/SF			
HD	40/50	ΟΡΥΚΤΕΛ.	16,50	173,0		100	245	-18	0,897		SF/CC			
DIESEL SIGMA	30	ΟΡΥΚΤΕΛ.	11,80	105,0		100	235	-21	0,892		CD/SF			
DIESEL SIGMA	40	ΟΡΥΚΤΕΛ.	15,70	160,0		100	250	-18	0,897		CD/SF			
DIESEL SIGMA	50	ΟΡΥΚΤΕΛ.	21,30	250,0		100	258	-15	0,900		CD/SF			